Introducing the all new

RUSBX2 REMOTE DUAL USB CHARGING KIT



- $\sqrt{\mbox{ Dual USB 2.0 Amp Charging and Data Adapter}}$
- $\sqrt{2}$ x Type A to Type B cables
- $\sqrt{}$ Anodized Aluminum Wall Plate with 2 x Type A Commercial USB ports.
- $\sqrt{\text{Low Votlage Contractor Installation.}}$
- $\sqrt{\mbox{Forward Compatible}}$ with charging technologies
- $\sqrt{\text{Installs in a standard outlet or electrical switch box}}$
- $\sqrt{\text{Highest quality components throughout}}$
- $\sqrt{}$ Install Locally at rack location or up to 1000 Ft for Charging and Data Transmission.
- $\sqrt{\text{Easy to install}}$ Terminals are marked with cable color.
- $\sqrt{\text{Weather Resistant Design}}$





RUSBX2

REMOTE DUAL USB CHARGING KIT

Technical Information



RUSBX2 - Rear View



RUSBX2 - LR Long run kit Breakout PC Board.

RUSBX2 Technical Specifications

USB Specifications

USB 2.1 AMP Type A

General

Standard:

Temperature Range: -20°C to +55°C.

Power Required: Local power via AC/DC adapter 5Vdc / 2 x 2.1 amp outputs

Dimensions: 4.5" L x 2.75" W x 1.25" Deep