Octasound®
S O U N D   A B O V E   A L L

Features:

- Provides 1.35" of recess for low voltage devices
- Protects low voltage devices/controllers from impacts
- Invisible mounting hardware
- Secure optional lockable door (SMLV-2-LD)
- Flush mountable with added FA-1 flange adapter
- 6 Knockouts for 1/2" Conduit (2 Top, 2 Bottom, and 2 Back)
- Compatible with RAMX2, RABX2, RAAX2, RUSB2 Modules
- Four rear mounting holes, mounting screws not included
- 16 Gauge Steel, black powder epoxy finish
- Mounts onto countertops or wall
- Recess option with added FA-1 Flange

Ordering Info:

SMLV-2 - Surface Mount Low Voltage Vandal Case Single Gang
SMLV-2-LD - Add Locking Door

A & E Specifications:

Vandal case shall be KDM part # _____ . The case shall
be fabricated from 11 guage steel and have a black powder
epoxy finish. The case shall be 7" x 5.75" x 3.15". The case shall
provide 2 top, 2 bottom, and 2 rear knockouts for 1/2" coduit.

SMLV-2
Shown with RABX2 mixer and RAAX2 amplifier installed.

SMLV-2-LD
Shown with RAMX2 mixer and RABX2 mixer

by
KDM

SMLV-2-LD
Surface Mount Low Voltage
Single Gang Vandal Case
With Locking Door

SMLV-2
Surface Mount Low Voltage
Single Gang Vandal Case

3.15"

7.125"

5.75"

by
KDM